Copyright MWE NA Inc., all rights reserved. Reproduction or other use Technical drawings are subject to change without notice. of these designs without written consent from MWE NA Inc. is prohibited. All millimeter dimensions are exact and supersede inch conversions. \*17.5mm [11/16"] Please specify on purchase order. ST.2100 42mm [1 11/16"] Please specify Ø50 or \*Wall Projection
Standard wall projection 17.5mm (wall to center rail)
17.5mm - 52.5mm available Ø60mm by purchase order Please Note: ST.1016.PR 37.5mm [1 1/2"] 42.5mm [1 11/16"] 17.5mm [11/16"] Anti-jump wheel is adjustable via the eccentric hole. 22.5mm [7/8"] 47.5mm [1 7/8"] 52.5mm [2 1/16"] 27.5mm [1 1/16"] ST.3016.PR 0 ST.2000 MWE wheel assemblies are suitable for all US standard door thicknesses! Height Specify door thickness on purchase Adjustability Projection of center rail to wall will be 100mm [3 15/16"] calculated. +/- 3mm [1/8"] 20mm [13/16"] 30mm [1 3/16"] 8mm/10mm [3/8"]/12mm ESG Tempered Glass ST.4006 - ST.4012 Maximum door weight 231 Lbs. 22mm [7/8"] See Details ST.2000 150mm [5 7/8"]



Prepared By: AB

Date Prepared: January 2023

**STAINLESS** 

Buy Online At www.StainlessDoorHardware.com



Email: sales@mwe-na.com www.mwe-na.com